

# Analyzing the Effect of Footprint Size and Spacing on ICESat-II Accuracy

B. Csatho<sup>1</sup>, T. Schenk<sup>1,2</sup>, T. Yoon<sup>1</sup>, G. Babonis<sup>1</sup>, J. Rich<sup>1</sup>, S. Nagarajan<sup>2</sup>, C. J. van der Veen<sup>3</sup>

<sup>1</sup>University at Buffalo


<sup>2</sup>The Ohio State University

<sup>3</sup>University of Kansas

Csatho, Schenk et al., 09/29/2008

Analyzing ICESat-II design parameters

4



### **Previous Work**

van der Veen, C. J., W. B. Krabill, B. Csatho, and J. F. Bolzan, 1998. Surface roughness on the Greenland ice sheet from airborne laser altimetry. Geophysical Research Letters, 25(20), 3887-3890.

van der Veen, C.J., Y. Ahn, B. Csatho, E. Mosley-Thompson and W.B. Krabill, in review. Surface roughness over the northern half of the Greenland ice sheet from airborne laser altimetry. Journal of Geophysical Research, Earth Surface


垂

Csatho, Schenk et al., 09/29/2008

Analyzing ICESat-II design parameters

3






- Roughness map of northern Greenland from ATM profiles
- Contour lines = black; transects= grey
- Roughness is estimated as the standard deviation of the residual obtained by fitting 500 m long segments
- Unit is "cm"


(from van der Veen et al., submitted)

Csatho, Schenk et al., 09/29/2008

Analyzing ICESat-II design parameters









Csatho, Schenk et al., 09/29/2008

### ICESat-II Performance Assessment

Analyzing ICESat-II design parameters

- Input: ATM profile, 1-m horizontal resolution
- Simulation of ICESat-II measurements by using ray-tracing
- Comparison of simulated ICESat measurements with "ground-truth" measurements to assess the effect of varying footprint size and spacing



### Concept of the waveform simulator

#### Simulates space-time waveforms:

- Computes the number of photons collected by the receiver as a function of time.
- Computes the travel time between the laser altimeter and the terrain and the energy distribution of the returned pulse.
- Handles various terrain data types:
  - Regularly spaced data, irregularly spaced data, profiler data



Csatho, Schenk et al., 09/29/2008

Analyzing ICESat-II design parameters


q





## **Algorithms**

- Tessellate the footprint under the laser beam into cells.
  - · Compute the amount of incident energy for each cell.
  - Determine contours equivalent to the travel time quantization.
  - · Compute the area enclosed by the contours.
  - Convert the area into energy.
  - Convert the returned energy into the number of photons.
- Repeat the above process for all cells.











# Experiment Design Surface Reconstruction

- Elevations are interpolated from simulated ICESat observations and compared with elevations of deterministic ice surface estimated from ATM profiler measurements. Zero RMS difference would mean perfect surface reconstruction. Smooth surface is obtained from ATM observations by fitting a quadratic function within a 400 meter moving window to remove stochastic signal/ surface roughness.
- Elevations are compared:
  - at locations of ICESat measurements
  - between ICESat observations (max interpolation error):
    - Linear interpolation of two neighboring ICESat elevations
    - Quadratic fitting to four neighboring ICESat observations

## **Change Detection Experiment**

 Repeat ICESat surface elevation measurements are being simulated along the same ATM profiles, but at different locations. Elevation change equals to zero and difference characterizes the error in change detection.

函

Csatho, Schenk et al., 09/29/2008


Analyzing ICESat-II design parameters


15





# Jakobshavn drainage basin low/high elevations









































Csatho, Schenk et al., 09/29/2008

Analyzing ICESat-II design parameters

31

